


COLOR: \_\_\_\_\_

CEILING HEIGHT



COLOR MATCH CAULK  
(21C002XXX)

TUBES REQ'D: \_\_\_\_\_

NOTE: TRIMS ARE ONLY AVAILABLE  
FOR .040 AND .060 THICK  
ACROVYN SHEETS

INSTALLED WITH "WATER  
BASED MASTIC" OVER  
"SEALING PRIMER"  
(90M064001)  
(90M055001)

.075N ACROVYN  
WALL COVERING

BASE (BY  
OTHERS)

2" FOR FIELD  
VARIATION

WAINSCOT  
HEIGHT

MATERIAL TO BE SUPPLIED IN 4'x8' OR 4'x10' SHEETS

NO. 4'x 8' SHEETS REQ'D.: \_\_\_\_\_

NO. 4'x 10' SHEETS REQ'D.: \_\_\_\_\_

# .075N ACROVYN AT PARTIAL HEIGHT

### GENERAL NOTES:

- 1) STANDARD SHEET SIZES: 4'x8' OR 4'x10' WITH MINIMUM THICKNESS.
- 2) .075N ACROVYN WALL COVER IS SUPPLIED WITH A STANDARD SUEDE TEXTURE.
- 3) TO INSURE PROPER INSTALLATION OF .075N ACROVYN COVERING, USE INSTALLATION SHEETS INCLUDED WITH EACH HARDWARE SHIPMENT.
- 4) COLOR SELECTION MUST BE INCLUDED WITH THE APPROVED DRAWINGS TO PREVENT ANY DELAYS IN THE SHIPMENT OF MATERIALS.
- 5) ACROVYN WALL COVERING IS AVAILABLE IN ANY OF C/S STANDARD COLORS.

PROJECT:

REVISION:

JOB NO.:

F&F:

CUSTOMER:

REP:

DATE:

DRAWN BY:

SHEET NO:



**Construction Specialties™**

6696 Route 405 Highway, Muncy PA 17756  
(800) 233-8493 • Fax (570) 546-4692 • www.csgroup.com