



Acrovyn®

Acrovyn 4000 2-Hour Rated Flush Mounted Corner Guard UL Specifications



SPECIFICATION DATA

TEST STANDARD

UL-263 (E-119)

UL® CLASSIFICATION

2- Hour Rating

UL® DIRECTORY REFERENCE

- Fire Resistance Directory (Current Year)
- Fire Resistance (XHBN)
- UL® SYSTEM NO. CG-S-0003
- UL® Fire Number R-13368

NATIONAL CODE REFERENCE

- International Building Code
- Life Safety Code (NFPA 251)
- BOCA (Sec. 913.4.2)
- Standard Building Code (Sec. 705.4.6.1)
- Uniform Building Code (Sec. 7.1)

MATERIAL RATING

- = 2-Hour Rating
- = 2-Hour Rating
- = 2-Hour Rating
- = 2-Hour Rating
- = 2-Hour Rating

RESTRICTIONS

Assembly must be installed in accordance with UL® system detail CG-S-0002.

UL® MARKING (LABEL)

- 1 Label per individual corner guard fire barrier.



Note: A UL label means the certified products are included in a yearly follow up/audit program so UL can ensure the company continues to provide the same quality product originally tested.



To download details, specs & photos visit www.c-sgroup.com
For technical and design assistance call 800-233-8493.

©Copyright 2010 Construction Specialties, Inc.

Construction Specialties, Inc. reserves the right to make design changes or withdraw any design without notice.