



Acrovyn®

Wall Covering UL Specifications



SPECIFICATION DATA

TEST STANDARD

UL-723 (ASTM-E84)

UL® CLASSIFICATION

Flame Spread 20
Smoke Development 400

UL® DIRECTORY REFERENCE

- Building Materials Directory (Current Year)
- Wall Covering (BWSZ)
- UL® Fire Number R-7821

NATIONAL CODE REFERENCE

- BOCA (Sec. 803.4)
- Life Safety Code (Sec. 6-5.2)
- Standard Building Code (Sec. 803.2)
- Uniform Building Code (Sec. 801)

MATERIAL RATING

- = Class I
- = Class A
- = Class A
- = Class I

RESTRICTIONS

Wall covering must be applied with Acrovyn Interiors Heavy Duty Water Based Mastic Adhesive at an application rate of 80 ft²/gal.

UL® MARKING (LABEL)

- 1 Label per Shipping Carton.

	CLASSIFIED WALL COVERING SURFACE BURNING CHARACTERISTICS	
	Applied to Inorganic Reinforced Cement Board	
91L8	SEMI-RIGID ¹ .035 in. Max. Thk.	UNBACKED ² .060 in. Max. Thk.
Flame Spread	10	20
Smoke Developed	20	450
¹ Applied with Super-Tek "CS-2000" adhesive at an application rate of 235 sq.ft./gal. or Roman Adhesives "PRO-732" adhesive at an application rate of 140 sq.ft./gal. ² Applied with Acrovyn Interiors "Water Base Mastic" at an application rate of 80 sq.ft./gal.		



To download details, specs & photos visit www.c-sgroup.com
For technical and design assistance call 800-233-8493.

©Copyright 2008 Construction Specialties, Inc.

Construction Specialties, Inc. reserves the right to make design changes or withdraw any design without notice.