

MATERIAL SAFETY DATA SHEET

MSDS Name: COLORFLEX II CF9001 AND ALL COLORS

Version Number: 1

Revision Date: January 1, 2010

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: COLORFLEX II
Proper Shipping Name: CAULK
HMIS Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPE: B

Company Name: KAMPEL ENTERPRISES, INC.
8930 CARLISLE ROAD
WELLSVILLE, PA 17365-0157
PH: 717-432-9688
Emergency Phone: 1-800-457-4280 / 1-352-323-3500

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredients Name	CAS Number	Percent	TSCA
----------------------------	------------	---------	------

No OSHA Hazardous Ingredients known at this time.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: High Viscosity Caulk
Appearance / Color: Various Colors
Solubility (in water): Yes
pH Value, +/- .3: 7.5
Boiling Range: 212.°F (100. °C)
Vapor Pressure (mmHg): 15. @ 68. °F (20. °C)
Evaporation Rate: 0.5 times Slower than n - Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight: approximately 20.%
% Volatile, Volume: approximately 30.%
Specific Gravity: 1.54989
VOC (less H2O or exempt): < 20 Gr / L (1%)

Note:

Odor: Mild acrylic Odor Freeze Point: 32 ° F

SECTION IV - FIRE FIGHTING MEASURES

Flammability Class: N /A
Flash Point: Not Available
Explosive Range (LEL/UEL): Not Applicable

EXTINGUISHING MEDIA:

Dry Chemical - Carbon Dioxide - Foam - Water Fog
Will not burn in wet state.

SPECIAL FIRE FIGHTING PROCEDURES:

Water may be used to cool and protect exposed containers. Caution should be taken because uncured material is water soluble.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may burst when exposed to extreme heat or fire.

SECTION V - HEALTH HAZARD DATA

Route	Species	Exposure and Dose
-------	---------	-------------------

ROUTES OF ENTRY:

ENTRY THROUGH...Inhalation and skin most likely.

CARCINOGENICITY

NTP?	N/E	I	IARC Monographs?	N / E	I	OHSA?	NO
------	-----	---	------------------	-------	---	-------	----

EFFECTS OF OVEREXPOSURE

Inhalation: May cause nose or throat irritation.
Skin / Eye Contact: May cause irritation.
Ingestion: Swallowing large amounts may cause nausea, vomiting. (an unlikely route of entry)

FIRST AID MEASURES

Inhalation: If affected by inhalation, remove to fresh air.
Eye Contact: Flush with water for at least 15 minutes, and get prompt medical attention.
Skin Contact: Wash skin thoroughly with soap and water.
Ingestion: Drink water, and get medical attention.

N / A = Not Applicable N / Av = Not Available N / E, N / est = Not Established

SECTION VI - STABILITY AND REACTIVITY

Stability: Product is stable under normal storage conditions
Hazardous Polymerization: Will not occur under normal conditions

INCOMPATIBILITY:

None

CONDITIONS TO AVOID:

None

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce oxides of carbon and oxides of nitrogen when burned.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES

STEPS TO BE TAKEN IN CASE OF SPILL:

Wear appropriate protective clothing. Add dry absorbent and shovel or sweep up. Place in an appropriate container and seal.

WASTE DISPOSAL METHOD:

Dispose of in accordance with Federal, State, and Local regulations.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL

RESPIRATORY PROTECTION:

NIOSH respirators recommended if vapors and mists are generated.

VENTILATION:

Local exhaust is recommended for safe practice.

PROTECTIVE CLOTHING:

Gloves and clothing should be worn to prevent repeated skin contact.

EYE PROTECTION:

Eye protection should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep from freezing. Keep away from heat.
Keep containers closed when not in use. Avoid prolonged or repeated contact with skin.

KEEP OUT OF THE REACH OF CHILDREN.

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

GROUND TRANSPORT (DOT) - DOMESTIC

Caulking compound, Non Regulated

AIR TRANSPORT (DOT) - DOMESTIC

Caulking compound, Non Regulated

AIR TRANSPORT (IATA) - INTERNATIONAL

Caulking compound, Non Regulated

MARINE - OCEAN TRANSPORT (IMDG)

Caulking compound, Non Regulated

SECTION X - REGULATORY INFORMATION

All Chemical substances are TSCA listed.
California PROP. 65 Chemicals: none known

Disclaimer:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his / her own investigation to determine the suitability of the information or products for their particular purpose, for the protection of the environment, and the health and safety of the users of this material.

