

# C/S BRJ/BRJW SERIES SPEC DATA

## C/S Expansion Joint Systems

### PRODUCT DESCRIPTION

BRJ and BRJW are flexible roof joint covers which utilize flexible membrane applied to support foam, and are secured with a factory-attached metal flange.

### BASIC USES

Roof expansion joint cover.

### TECHNICAL DATA

<u>Flanges</u>	<u>Thickness</u>
Galv. Steel	26 Ga.
Stainless Steel*	0.018"
Aluminum*	0.032"
Copper*	16 Oz.

(\*=Optional flanges – Galvanized is standard)

<u>Membrane</u>	<u>Thickness</u>	<u>Color</u>
EPDM	60 Mil	Black
Neoprene*	60 Mil	Black

(\*=Optional material – EPDM is standard)

<u>Support Foam</u>	
K Factor	0.25 @ Ambient
Thickness	Varies per Joint Size

<u>PVC secondary seal</u>		
Material	PVC	ASTM D2000
Durometer	65A	
Color	black	

### STANDARD FINISH

Membrane – Black, Flanges – As fabricated.

### PRECAUTIONS

Refer to Material Safety Data Sheet for detailed health and safety information prior to use.

### WARRANTY

C/S warrants that its products are manufactured free of defects and conform to the technical data listed. Under this warranty, we will replace (at no charge) any material proven defective when applied in accordance with our written instructions for applications recommended by us as suitable for subject products. C/S shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.



To download details and specifications visit [www.c-sgroup.com](http://www.c-sgroup.com).  
For technical and design assistance call (800) 233-8493.