

C/S GFW SPEC DATA

C/S Expansion Joint Systems

PRODUCT DESCRIPTION

The C/S GFW is a dual-gasketed system with extruded aluminum base frames and center plate designed for use as a wall joint cover assembly. Model GFW utilizes an exposed aluminum center plate and santoprene gaskets. The aluminum center plate is retained by a series of stainless steel spring clips, spaced 18" o.c.

BASIC USES

Wall expansion joint cover. Ideal for use in hospitals and other conditions requiring a flush joint system.

TECHNICAL DATA

Aluminum

Material	6061-T6	ASTM B221
Santoprene primary seal		
Dual Durometer	221-87A, 221-55A	ASTM D2000
Color	4 standard	

Model	Size	Joint Width	Exposed Surface	Tension & Compression Movement	Seismic Movement
GFW	200	2.00	6.50	1.00	1.00
	300	3.00	10.00	1.50	1.50
	400	4.00	11.00	2.00	2.00
GFW C	200	2.00	4.25	0.50	0.50
	300	3.00	6.50	0.75	0.75
	400	4.00	7.50	1.00	1.00

STANDARD FINISH

Gasket of color selected. Mill finish for any exposed aluminum.



Black White Gray Greige

PRECAUTIONS

Refer to Material Safety Data Sheet for detailed health and safety information prior to use.

WARRANTY

C/S warrants that its products are manufactured free of defects and conform to the technical data listed. Under this warranty, we will replace (at no charge) any material proven defective when applied in accordance with our written instructions for applications recommended by us as suitable for subject products. C/S shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.



To download details and specifications visit www.c-sgroup.com.
For technical and design assistance call (800) 233-8493.