



# Expansion Joint Covers

## GTR-S & GTRW-S Series GTR-B & GTRW-B Series

### Technical Data:

#### Aluminum

- Extrusion – C/S uses multiple alloys & tempers which are established to be the most appropriate for the given use of individual parts. Will be one of the following: (6063-T5, T6, T52) (6061-T5, T6, T51) (6105-T5, T6) (6005-T5) (6005A-T5, T61)

#### Bronze

- C28000 Muntz Metal ASTM B455

#### Stainless Steel

- Type 304 ASTM A167, A240A, A240M

#### Primary Seal


- Dual Durometer 65 Shore A, 90 Shore A, ASTM D2000
- Available in 4 colors.

#### Turnbar

- Injection Molded, Glass-Reinforced Plastic

#### Standard Loading

- 500 lbs.



### Product Description:

This dual gasket, flush floor cover is ideal for areas with larger movement requirements and where a bronze or stainless finish is desired.

### Use This Cover For:

- Applications where a flush cover is preferred.
- Cover offers a 1/8" recessed center plate to accept bronze or stainless insert.
- Where light wheeled equipment is to be used.
- Where hygiene is important.

### Performance Characteristics:

The dual durometer thermoplastic gasket has rigid edges designed to lock into the aluminum side frames. This prevents hairline gaps from opening between the gasket and frame ensuring a hygienic seal. The softer center section of the gasket allows full movement without the need for grooves in the top surface which collect dirt. The rigid edges also prevent the gasket from being cut by heavy rolling loads that tend to destroy conventional gaskets. Dual gaskets allow for greater expansion and compression during movement. Durable self-centering aluminum plate spans joint opening.

### Standard Finishes:


Stainless Steel – No. 4 finish. Bronze – Satin finish. Gasket is available in Black, White, Gray, & Greige. Aluminum in contact with concrete/masonry will have a 2 mil heavy metal free high solids primer.

### Installation Guidelines:


The blockouts must be prepared to receive the joint cover. Depth may be adjusted as needed to accommodate a floor finish material when required. Attach frames in blockout with C/S supplied screws. Slide in turnbars and align with holes in cover plate. Screw cover plate into turnbars and insert gaskets. For complete installation instructions, please visit [www.c-sgroup.com](http://www.c-sgroup.com).

To download detail, specs & photos visit [www.c-sgroup.com](http://www.c-sgroup.com)  
For technical and design assistance call 800-233-8493.

| MODEL       | JOINT WIDTH   | MINIMUM OPENING | MAXIMUM OPENING | EXPOSED SURFACE | BLOCKOUT WIDTH | BLOCKOUT HEIGHT |
|-------------|---------------|-----------------|-----------------|-----------------|----------------|-----------------|
| GTR-200S/B  | 2.00" (51mm)  | 1.25" (32mm)    | 3.75" (95mm)    | 6.50" (165mm)   | 2.25" (57mm)   | 0.63" (16mm)    |
| GTR-300S/B  | 3.00" (76mm)  | 1.25" (32mm)    | 6.00" (152mm)   | 10.00" (254mm)  | 3.50" (89mm)   | 0.63" (16mm)    |
| GTR-400S/B  | 4.00" (102mm) | 1.25" (32mm)    | 6.25" (159mm)   | 11.00" (279mm)  | 3.50" (89mm)   | 0.63" (16mm)    |
| GTRW-200S/B | 2.00" (51mm)  | 1.00" (25mm)    | 3.00" (76mm)    | 4.25" (108mm)   | 2.25" (57mm)   | 0.63" (16mm)    |
| GTRW-300S/B | 3.00" (76mm)  | 1.50" (38mm)    | 4.50" (114mm)   | 6.50" (165mm)   | 3.50" (89mm)   | 0.63" (16mm)    |
| GTRW-400S/B | 4.00" (102mm) | 2.50" (64mm)    | 5.50" (140mm)   | 7.50" (191mm)   | 3.50" (89mm)   | 0.63" (16mm)    |



GTR-S/B (TYP.)



GTRW-S/B (TYP.)