

C/S SF/SC EXTERIOR SEAL SPEC DATA

C/S Expansion Joint Systems

PRODUCT DESCRIPTION

SF and SC are gasketed exterior wall covers comprised of extruded aluminum frames, santoprene primary seal and PVC secondary seal.

BASIC USES

Exterior wall expansion joint cover.

TECHNICAL DATA

<u>Aluminum</u>	<u>Value</u>	<u>ASTM Ref.</u>
Material	6063-T5	ASTM B221
<u>Santoprene Primary Seal</u>		
Material	591-73	
Durometer	73 Shore A	ASTM D2240
Color	4 standard	
Tensile Strength	990 psi (min.)	ASTM D412
Elongation @ Break	510%	ASTM D412
Tear Strength	210 lbf/in	ASTM D624
Compression Set (168 hr.)	22% @ 73°F	ASTM D395
Brittle Point	-76°F	ASTM D794
Ozone Resistance	No Cracks	ASTM D1149
UV Resistance	Very Good	
<u>PVC secondary seal</u>		
Material	PVC	ASTM D2000
Durometer	65A	
Color	black	

STANDARD FINISH

Gasket of color selected. (Standard: Black, White, Gray, Greige)

PRECAUTIONS

Refer to Material Safety Data Sheet for detailed health and safety information prior to use.

WARRANTY

C/S warrants that its products are manufactured free of defects and conform to the technical data listed. Under this warranty, we will replace (at no charge) any material proven defective when applied in accordance with our written instructions for applications recommended by us as suitable for subject products. C/S shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.



To download details and specifications visit www.c-sgroup.com.
For technical and design assistance call (800) 233-8493.