

C/S SRJ/SRJW SERIES

SPEC DATA

C/S Expansion Joint Systems

PRODUCT DESCRIPTION

SRJ and SRJW are aluminum roof covers comprised of extruded aluminum components, spring steel turnbars, duroflex gaskets and polyethylene vapor barrier.

BASIC USES

Roof expansion joint cover.

TECHNICAL DATA

Aluminum

Frame	6063-T52	ASTM B221
Cover plate	3003H14	ASTM B209

Duroflex gasket

Material	PVC	ASTM D2000
Durometer	80A	
Color	black	

Turnbar

Material	1075 Blue Temper Spring Steel	
Hardness	RC 44-47	
Finish	"A" Coating (Corrosion Protection)	

Vapor Barrier

Material	Polyethylene	ASTM E-1745-97
Color	Black	
3" Tensile Strength	275 lb.	ASTM-882
Puncture Strength	72 lb.	ASTM-4833
PPT Resistance	33 lb.	ASTM-2582

STANDARD FINISH

Mill finish.

PRECAUTIONS

Refer to Material Safety Data Sheet for detailed health and safety information prior to use.

WARRANTY

C/S warrants that its products are manufactured free of defects and conform to the technical data listed. Under this warranty, we will replace (at no charge) any material proven defective when applied in accordance with our written instructions for applications recommended by us as suitable for subject products. C/S shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of the product.



To download details and specifications visit www.c-sgroup.com.
For technical and design assistance call (800) 233-8493.