

OPENING SINGLE _____ PAIR _____ DOUBLE _____ DOUBLE _____ ACTING _____ EGRESS _____		PROJECT _____ CUSTOMER _____ QUOTE # _____ DATE _____							
FIRE RATING "S" Label _____ (20, 45, 60, 90) Temp. Rise _____		FRAME OPENING SIZE (WIDTH X HEIGHT) _____		PREFIT DOOR SIZE (WIDTH X HEIGHT) _____		BLOCKING _____ DOOR FACE ACROVYN COLOR # _____ DOOR EDGE ACROVYN COLOR # _____			
LITE VISIBLE GLASS (W x H) _____ OR CUTOUT ONLY (W x H) _____ DISTANCE FROM TOP RAIL (in) _____ DISTANCE FROM LOCK STILE (in) _____ -OR- LIGHT KIT TYPE (IF TO BE PROVIDED BY CS) METAL: BEIGE (PC) _____ METAL: ACROVYN WRAPPED _____ METAL: PAINTED TO MATCH _____ WOOD: FLUSH BEAD _____ WOOD: LIPPED BEAD _____ * SEE ATTACHED SHEET FOR ADDITIONAL LIGHT KIT INFORMATION. CIRCLE IF CENTERED									
GLASS OPTIONS (CIRCLE REQUIRED OPTION) 1/4" TEMPERED (NR) 1/4" FIREGLASS 20 (20) 1/4" SUPERLITE I (20) 1/4" SUPERLITE I-W (20, 45, 60, 90) 3/8" FIRELITE NT (20, 45, 60, 90) 5/16" FIRELITE PLUS (20, 45, 60, 90) 7/8" KERALITE ULTRA (LOW TEMP RISE) (Optional - 45, 60, 90) OTHER _____		TOTAL DOORS THIS PAGE: _____							
SUPPLIED BY OTHERS? Y/N _____ INSTALLED BY CS? Y/N _____		HINGE (*REQUIRED FOR FABRICATION) MANUFACTURER* _____ MFG. MODEL NO.* _____ SIZE (HEIGHT x THICKNESS)* _____ TEMPLATE NO.* _____		EDGE TYPE: HINGE: ☐ BEVELED ☐ SQUARE ☐ RADIUS LATCH: ☐ BEVELED ☐ SQUARE ☐ RADIUS		LOCKSET (*REQUIRED FOR FABRICATION) MANUFACTURER* _____ MFG. MODEL NO.* _____ CYLINDRICAL* _____ MORTISE* _____ TEMPLATE NO.* _____		FLUSHBOLT (MFG., MODEL, & TEMPLATE NO.) _____ CONCEALED CLOSER / STOP (DEGREE OF OPENING, MFG., MODEL & TEMPLATE NO.) _____ EXIT DEVICE (MFG., MODEL & TEMPLATE NO.) _____ DEAD BOLT (MFG., MODEL & TEMPLATE NO.) _____ DOOR BOTTOM (MFG., MODEL & TEMPLATE NO.) _____ MISC. HARDWARE (TYPE, MFG., MODEL, & TEMPLATE NO.) _____	
OPTIONAL PROTECTION PLATES STAINLESS STL. ☐ SIZE (HEIGHT) _____ PUSH SIDE _____ PULL SIDE _____ DOOR FRAME PROTECTION? Y/N _____		PAGE _____ OF _____							