


**PEDIMAT WITH TAPERED VINYL**

INSERT STYLE:      INSERT COLOR: PLEASE ADVISE      CATALOG NUMBER: M1      PART NUMBER:


NO.	REVISION	DATE	BY
NO.	F&F RELEASE	DATE	BY

- |   |   |  |
|---|---|--|
|  |  |  |
| EXTERIOR<br>CARPET<br>M1EC<br>19C018XXX   | HEAVY-DUTY<br>CARPET<br>M1HC<br>19C010XXX   | RUBBER<br>M1V<br>19V022501<br>#8501 BLACK  |


**PEDIMAT INSERT STYLES**



**TYPICAL PLAN VIEW**



**SECTION Y-Y**



**SECTION X-X**

- HOOK & LOOP ANCHOR (90H006010)  
18" O.C. IN TRAFFIC DIRECTION  
(ONLY WHERE SPLIT IS REQUIRED)

**NOTES:**

\*ALL SURFACES IN CONTACT WITH MASONRY ARE TO RECEIVE A COAT OF ZINC CHROMATE PRIMER

\*MAX. SINGLE GRID SIZE NOT TO EXCEED 12'-0" (3.66M) IN WIDTH (DIM "A") OR 100 SQUARE FEET

\*PLEASE VERIFY TRAFFIC DIRECTION

\*ADDITIONAL SPECIFICATIONS ARE CONTAINED IN THE LATEST C/S CATALOG OR AT C-SGROUP.COM AND ARE CONSIDERED PART OF THIS TRANSMITTAL.

\*PEDIMAT SHALL BE ABLE TO SUPPORT A 350 LB. ROLLING LOAD. LARGER LOADING MAY BE ACCOMODATED. CONTACT C/S SALES WITH SPECIFIC LOADING REQUIREMENTS.

**CS Construction Specialties™**  
 6696 Route 405 Highway, Muncy PA 17756  
 (800) 233-8493 • Fax (570) 546-4692 • www.c-sgroup.com

PLEASE VERIFY ALL	QTY	MARK #	LOCATION	MODEL	DIM 'A' WIDTH	DIM 'B' LENGTH	FINISH	NOTES

PROJECT:		
LOCATION:		
CONTRACTOR:		
AGENT:		SHT:
DRG. BY:	DATE:	JOB NO.: